### Auto Klene Neon Red /blue/yellow

### **Auto Klene Solutions**

Chemwatch: **73-5405** Version No: **3.1.1.1** 

Safety Data Sheet according to HSNO Regulations

Chemwatch Hazard Alert Code: 2

Issue Date: 10/01/2017 Print Date: 12/01/2017 S.GHS.NZL.EN

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

# Product Identifier Product name Auto Klene Neon Red /blue/yellow Synonyms Not Available Other means of identification Not Available

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Concentrated Sealer Wax.

### Details of the supplier of the safety data sheet

Registered company name	Auto Klene Solutions
Address	1/83 Merrindale Drive VIC Croydon 3136 Australia
Telephone	+61 3 8761 1900
Fax	+61 3 8761 1955
Website	https://www.autoklene.com/msds/
Email	Not Available

#### **Emergency telephone number**

Association / Organisation	Not Available	
Emergency telephone numbers	131 126 (Poisons Information Centre)	
Other emergency telephone numbers	0800 764 766 (New Zealand Poisons Information Centre)	

### **SECTION 2 HAZARDS IDENTIFICATION**

### Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

### CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	1		
Toxicity	0		0 = Minimum
Body Contact	2		1 = Low 2 = Moderate
Reactivity	1		3 = High
Chronic	0		4 = Extreme

Classification [1]	Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria	6.3A, 6.4A	

### Label elements

GHS label elements



SIGNAL WORD WARNING

### Hazard statement(s)

H315	Causes skin irritation.
H319	Causes serious eye irritation.

Chemwatch: 73-5405 Page 2 of 9 Issue Date: 10/01/2017 Version No: 3.1.1.1

### Auto Klene Neon Red /blue/yellow

Print Date: 12/01/2017

P280 Wear protective gloves/protective clothing/eye protection/face protection.

### Precautionary statement(s) Response

P362	Take off contaminated clothing and wash before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P332+P313	If skin irritation occurs: Get medical advice/attention.

### Precautionary statement(s) Storage

Not Applicable

### Precautionary statement(s) Disposal

Not Applicable

### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
70592-80-2	15-25	cocodimethylamine oxide
8001-54-5	<5	benzalkonium chloride
64-17-5	<5	ethanol
Not Available	1-3	dye
Not Available	1-3	perfume
	balance	#nonhaz
7732-18-5	balance	water

### **SECTION 4 FIRST AID MEASURES**

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

### Description of first aid measures

Description of first aid me	asures
Eye Contact	If this product comes in contact with the eyes:  Immediately hold eyelids apart and flush the eye continuously with running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.  Transport to hospital or doctor without delay.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If furnes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically. For acute or short-term repeated exposures to highly alkaline materials:

- $\blacksquare \ \ \, \text{Respiratory stress is uncommon but present occasionally because of soft tissue edema}.$
- Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- Oxygen is given as indicated.
- ▶ The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Pamage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

- ▶ Milk and water are the preferred diluents
- No more than 2 glasses of water should be given to an adult.
- ▶ Neutralising agents should never be given since exothermic heat reaction may compound injury.
- \* Catharsis and emesis are absolutely contra-indicated.
- \* Activated charcoal does not absorb alkali.
- \* Gastric lavage should not be used.

Supportive care involves the following:

Chemwatch: 73-5405 Page 3 of 9

Version No: 3.1.1.1

### Auto Klene Neon Red /blue/yellow

Issue Date: **10/01/2017**Print Date: **12/01/2017** 

- Withhold oral feedings initially.
- ▶ If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- ▶ Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

▶ Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

### **SECTION 5 FIREFIGHTING MEASURES**

### Extinguishing media

- ▶ Water spray or fog.
- Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

### Special hazards arising from the substrate or mixture

Fire Incompatibility	► Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Advice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>Avoid spraying water onto liquid pools.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>On combustion, may emit toxic furnes of carbon monoxide (CO).</li> <li>May emit acrid smoke.</li> <li>Mists containing combustible materials may be explosive.</li> <li>Combustion products include:         <ul> <li>carbon dioxide (CO2)</li> <li>nitrogen oxides (NOx)</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit corrosive furnes.</li> </ul> </li> </ul>

### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

### Personal precautions, protective equipment and emergency procedures

See section 8

### **Environmental precautions**

See section 12

### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>Wipe up.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	Moderate hazard.  Clear area of personnel and move upwind.  Alert Fire Brigade and tell them location and nature of hazard.  Wear breathing apparatus plus protective gloves.  Prevent, by any means available, spillage from entering drains or water course.  No smoking, naked lights or ignition sources.  Increase ventilation.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### **SECTION 7 HANDLING AND STORAGE**

### Precautions for safe handling

► DO NOT allow clothing wet with material to stay in contact with skin
<ul> <li>Avoid all personal contact, including inhalation.</li> </ul>
Wear protective clothing when risk of exposure occurs.

- Safe handling
- Use in a well-ventilated area.Prevent concentration in hollows and sumps.
- ► DO NOT enter confined spaces until atmosphere has been checked.

Chemwatch: **73-5405** Page **4** of **9** 

Version No: **3.1.1.1** 

### Auto Klene Neon Red /blue/yellow

Issue Date: **10/01/2017**Print Date: **12/01/2017** 

	<ul> <li>Avoid smoking, naked lights or ignition sources.</li> </ul>
	<ul> <li>Avoid contact with incompatible materials.</li> </ul>
	► Store in original containers.
	► Keep containers securely sealed.
	No smoking, naked lights or ignition sources.
Other information	▶ Store in a cool, dry, well-ventilated area.
	► Store away from incompatible materials and foodstuff containers.
	▶ Protect containers against physical damage and check regularly for leaks.
	<ul> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

#### Conditions for safe storage, including any incompatibilities

#### Suitable container

- ▶ Metal can or drum
- Packaging as recommended by manufacturer.
- ► Check all containers are clearly labelled and free from leaks.

Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates.

### Storage incompatibility

Avoid strong acids, bases.

▶ Avoid contact with copper, aluminium and their alloys.

### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### **Control parameters**

### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	ethanol	Ethyl alcohol (Ethanol)	1,880 mg/m3 / 1,000 ppm	Not Available	Not Available	Not Available

### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
benzalkonium chloride	Alkyl dimethylbenzyl ammonium chloride; (Benzalkonium chloride)	0.91 mg/m3	10 mg/m3	60 mg/m3
ethanol	Ethyl alcohol; (Ethanol)	Not Available	Not Available	15000 ppm

Ingredient	Original IDLH	Revised IDLH
cocodimethylamine oxide	Not Available	Not Available
benzalkonium chloride	Not Available	Not Available
ethanol	15,000 ppm	3,300 [LEL] ppm
dye	Not Available	Not Available
perfume	Not Available	Not Available
water	Not Available	Not Available

### **Exposure controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

### Appropriate engineering controls

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

### Personal protection











## Eye and face protection

- Safety glasses with side shields.
- ▶ Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable.

### Skin protection

### See Hand protection below

### ► Wear chemical protective gloves, e.g. PVC.

► Wear safety footwear or safety gumboots, e.g. Rubber

### Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

### Body protection

See Other protection below

# Page 5 of 9 Auto Klene Neon Red /blue/yellow

Issue Date: **10/01/2017**Print Date: **12/01/2017** 

Other protection

- Overalls
- ► P.V.C. apron.
- ▶ Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

Thermal hazards

Not Available

### Recommended material(s)

#### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Auto Klene Neon Red /blue/yellow

Material	СРІ
BUTYL	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NITRILE	С
NITRILE+PVC	С
PE/EVAL/PE	С
PVA	С
PVC	С
VITON	С

<sup>\*</sup> CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation.

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

### Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AK-AUS / Class1 P2	-
up to 50	1000	-	AK-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	AK-2 P2
up to 100	10000	-	AK-3 P2
100+			Airline**

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

### **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

### Information on basic physical and chemical properties

• •	· ·		
Appearance	Red/ yellow/ blue coloured liquid; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	0.9
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	6-7	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

### **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>

# Page 6 of 9 Auto Klene Neon Red /blue/yellow

Issue Date: **10/01/2017** Print Date: **12/01/2017** 

Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

### **SECTION 11 TOXICOLOGICAL INFORMATION**

SECTION 11 TOXICOLOG	SICAL INFORMATION				
Information on toxicologic	cal effects				
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.				
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.				
Skin Contact	The material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.  The material may accentuate any pre-existing dermatitis condition  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.				
Eye	This material can cause eye irritation and damage in some persons				
Chronic	Long-term exposure to the product is not thought to produce chronic nevertheless exposure by all routes should be minimised as a matter Prolonged or repeated skin contact may cause degreasing with dry				
Auto Klene Neon Red	тохісіту	IRRITATION			
/blue/yellow	Not Available	Not Available			
	TOXICITY	IRRITATION			
cocodimethylamine oxide	Not Available	Not Available			
		'			
	TOXICITY	IRRITATION			
benzalkonium chloride	Dermal (rabbit) LD50: 1560 mg/kg <sup>[2]</sup>	Eye (human): 0.05 mg SEVERE			
	Oral (rat) LD50: 240 mg/kg <sup>[2]</sup>	Eye (rabbit): 1mg/24h SEVERE			
		Skin (human): 0.15 mg/72h mild			
	TOXICITY	IRRITATION			
	Dermal (rabbit) LD50: 17100 mg/kg <sup>[1]</sup>	Eye (rabbit): 500 mg SEVERE			
ethanol	Inhalation (rat) LC50: 64000 ppm/4hr <sup>[2]</sup>	Eye (rabbit):100mg/24hr-moderate			
	Oral (rat) LD50: >1187-2769 mg/kg <sup>[1]</sup>	Skin (rabbit):20 mg/24hr-moderate			
		Skin (rabbit):400 mg (open)-mild			
	TOXICITY	IRRITATION			
water	Oral (rat) LD50: >90000 mg/kg <sup>[2]</sup>	Not Available			
Legend:	, ,	tte toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data			
	extracted from RTECS - Register of Toxic Effect of chemical Substa	ances			
COCODIMETHYLAMINE	Amine oxides are readily metabolised and excreted after oral intake. They produced no mortality or skin sensitization on exposure but caused reversible irritation of the eyes, skin and airways. They may also cause cataracts. Repeat dosing showed no abnormal changes except for diarrhoea and weight loss. They are not noted to cause cancer, reproductive, genetic or developmental defects.  The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.				
BENZALKONIUM CHLORIDE	ingestion", and "corrosive and very toxic to aquatic organisms". It ca	Alkyldimethylbenzylammonium chlorides are in the list of dangerous substances of council directive, classified as "harmful in contact with skin and on ingestion", and "corrosive and very toxic to aquatic organisms". It can cause dose dependent skin and eye irritation with possible deterioration of vision, possible sensitisation in those with pre-existing eczema. It does not cause cancer, genetic defect, foetal or developmental abnormality.			
COCODIMETHYLAMINE OXIDE & WATER	No significant acute toxicological data identified in literature search				
COCODIMETHYLAMINE OXIDE & ETHANOL	The material may cause skin irritation after prolonged or repeated ex scaling and thickening of the skin.	xposure and may produce on contact skin redness, swelling, the production of vesicles,			
COCODIMETHYLAMINE OXIDE & BENZALKONIUM CHLORIDE	scaling and thickening of the skin.  Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance.				

irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

Chemwatch: 73-5405 Page 7 of 9 Issue Date: 10/01/2017 Version No: 3.1.1.1 Print Date: 12/01/2017

### Auto Klene Neon Red /blue/yellow

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	✓	Reproductivity	0
Serious Eye Damage/Irritation	<b>✓</b>	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

🗶 – Data available but does not fill the criteria for classification

✓ – Data required to make classification available

O - Data Not Available to make classification

### **SECTION 12 ECOLOGICAL INFORMATION**

### Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
cocodimethylamine oxide	EC50	504	Crustacea	0.88mg/L	4
cocodimethylamine oxide	NOEC	504	Fish	0.5mg/L	4
benzalkonium chloride	LC50	96	Fish	0.32mg/L	4
benzalkonium chloride	EC50	48	Crustacea	0.018mg/L	4
benzalkonium chloride	EC50	96	Algae or other aquatic plants	0.056mg/L	4
benzalkonium chloride	EC50	24	Algae or other aquatic plants	0.0013mg/L	4
benzalkonium chloride	NOEC	1	Algae or other aquatic plants	0.0025mg/L	4
ethanol	LC50	96	Fish	42mg/L	4
ethanol	EC50	48	Crustacea	2mg/L	4
ethanol	EC50	96	Algae or other aquatic plants	17.921mg/L	4
ethanol	EC50	24	Algae or other aquatic plants	0.0129024mg/L	4
ethanol	NOEC	2016	Fish	0.000375mg/L	4
Legend:	Aquatic Toxicity Data (E	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data			

DO NOT discharge into sewer or waterways.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
water	LOW	LOW

### **Bioaccumulative potential**

Ingredient	Bioaccumulation
ethanol	LOW (LogKOW = -0.31)
water	LOW (LogKOW = -1.38)

### Mobility in soil

Ingredient	Mobility
ethanol	HIGH (KOC = 1)
water	LOW (KOC = 14.3)

### **SECTION 13 DISPOSAL CONSIDERATIONS**

### Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Product / Packaging ▶ Where in doubt contact the responsible authority.
  - Recycle wherever possible or consult manufacturer for recycling options.
  - ► Consult State Land Waste Authority for disposal.
  - Bury or incinerate residue at an approved site.
  - ► Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

### **SECTION 14 TRANSPORT INFORMATION**

disposal

### **Labels Required**

Issue Date: 10/01/2017 Print Date: 12/01/2017

Marine Pollutant

NO

**HAZCHEM** Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### **SECTION 15 REGULATORY INFORMATION**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002624	N.O.S. (Subsidiary Hazard) Group Standard 2006
HSR002535	Compressed Gas Mixtures (Subsidiary Hazard) Group Standard 2006
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2006
HSR002530	Cleaning Products (Subsidiary Hazard) Group Standard 2006
HSR002585	Fuel Additives (Subsidiary Hazard) Group Standard 2006
HSR002519	Aerosols (Subsidiary Hazard) Group Standard 2006
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2006
HSR002606	Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2006
HSR002644	Polymers (Subsidiary Hazard) Group Standard 2006
HSR002647	Reagent Kits Group Standard 2006
HSR002612	Metal Industry Products (Subsidiary Hazard) Group Standard 2006
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006
HSR002503	Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006
HSR002638	Photographic Chemicals (Subsidiary Hazard) Group Standard 2006
HSR002565	Embalming Products (Subsidiary Hazard) Group Standard 2006
HSR002578	Food Additives and Fragrance Materials (Subsidiary Hazard) Group Standard 2006
HSR002558	Dental Products (Subsidiary Hazard) Group Standard 2006
HSR002684	Water Treatment Chemicals (Subsidiary Hazard) Group Standard 2006
HSR002573	Fire Fighting Chemicals Group Standard 2006
HSR100425	Pharmaceutical Active Ingredients Group Standard 2010
HSR002600	Leather and Textile Products (Subsidiary Hazard) Group Standard 2006
HSR002605	Lubricants (Low Hazard) Group Standard 2006
HSR002571	Fertilisers (Subsidiary Hazard) Group Standard 2006
HSR002648	Refining Catalysts Group Standard 2006
HSR002653	Solvents (Subsidiary Hazard) Group Standard 2006
HSR002544	Construction Products (Subsidiary Hazard) Group Standard 2006
HSR002549	Corrosion Inhibitors (Subsidiary Hazard) Group Standard 2006
HSR002552	Cosmetic Products Group Standard 2006
HSR100757	Veterinary Medicine (Limited Pack Size, Finished Dose) Standard 2012
HSR100758	Veterinary Medicines (Non-dispersive Closed System Application) Group Standard 2012
HSR100759	Veterinary Medicines (Non-dispersive Open System Application) Group Standard 2012
HSR100628	Straight-chained Lepidopteran Sex Pheromone Group Standard 2012
HSR100580	Tattoo and Permanent Makeup Substances Group Standard 2011

### COCODIMETHYLAMINE OXIDE(70592-80-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

BENZALKONIUM CHLORIDE(8001-54-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

ETHANOL(64-17-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of

Chemicals

New Zealand Workplace Exposure Standards (WES)

New Zealand Inventory of Chemicals (NZIoC)

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

Chemwatch: 73-5405 Page 9 of 9 Issue Date: 10/01/2017 Version No: 3.1.1.1 Print Date: 12/01/2017

### Auto Klene Neon Red /blue/yellow

**Location Test Certificate** 

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

### **Approved Handler**

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

### **Tracking Requirements**

Not Applicable

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	N (cocodimethylamine oxide; ethanol; water; benzalkonium chloride)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water; benzalkonium chloride)
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

### **SECTION 16 OTHER INFORMATION**

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.